

5614 UR XX

Subway - Wall-mounted toilet with rimless flushing (Directflush) - 1.6/0.8 gpf (6/3 lpf)

Features

- Wall-mounted toilet with rimless flushing (Directflush)
- 14 5/8" x 22" (370 x 560 mm)
- 1.6/0.8 gpf (6/3 lpf)
- Washdown model
- Rear outlet
- Concealed trapway
- D-shape bowl

The bowl is to be used with In-wall tank/carrier from TOTO (WT152M DUOFIT IN-WALL TANK SYSTEM) or Geberit (# 111.335.00.5) to satisfy EPA WaterSense.

Optional CeramicPlus - CeramicPlus is a particularly easy-care and dirt-repellent surface. With ceramicplus water immediately forms droplets that simply flow off the surface, taking the dissolved dirt and limescale with them.



Codes / Standard applicable

- ADA compliant
- EPA - Watersense
- Meets and exceeds ASME A112.19.2/CSA B45.1 ASME A112.19.14
- Certifications: IAPMO(cUPC), EPA Watersense, City of Los Angeles and others
- Certifications: IAPMO(cUPC), State of Massachusetts
- Code Compliance: UPC, IPC, NSPC, NPC Canada and others



Colors - XX

- 01 = White Alpin
- R1 = White Alpin CeramicPlus

Product Specification

This wall-mounted toilet is made of vitreous china. The wall-mounted toilet is 22" (560mm) x 14 5/8" (370mm). The product has a concealed trapway and a D-shape bowl. The product is with ceramic plus. The product has a water use of 1.6/0.8. gpf (6/3 lpf). The wall-mounted toilet is Villeroy & Boch model 5614UR

Components

Included	
5614 UR XX	Wall-mounted toilet with rimless flushing (Directflush)
Required	
9M68 U1 01	WC-seat and cover
Optional	
9M68 U0 01	WC-seat and cover
9M78 U1 01	WC-seat and cover SlimSeat
9M78 U6 01	WC-seat and cover SlimSeat

Installation Notes

Install this product according to the installation manual.

Proper wall construction is required for best support of wall mounted toilets. V&B recommends the use of 3/4" greenboard (minimum thickness), instead of drywall, for wall area where toilet will be installed. Ceramic tile is recommended for finishing the surface.

Both the greenboard and ceramic tile must be properly sealed against wet conditions.

Technical Information

Water use	1.6/0.8 gpf (6/3 lpf)
Material	Vitreous china
Warranty	One year limited warranty
Min Water pressure	8 psi
Water surface	4" x 5" (100 x 130 mm)
Trap diameter	2" (50mm)
Trap seal	2 3/8" (60mm)
Minimum rough-in	7" (180 mm) rough-in
Outlet	Rear outlet
Shipping dimensions	17 1/8" x 25 9/16" x 18"

Technical Drawing

